

JOINTER SAFETY TEST #4

Name: _____ Score: _____ Term: _____ Date: _____

Directions: Fill in the blank with the best proper word that will complete the question. If it asks to explain do so as completely and accurately as possible.

1. Never surface stock less than _____ inches long.
- 2.-3. When working a piece of wood on the jointer, you need to follow the _____ inch rule, and must never get your hands any closer than that to the revolving _____ .
4. Never apply _____ to stock directly over the cutter - head.
5. Position _____ away from extreme ends of stock, and push through with a smooth, even motion.
6. The grain must run in the same direction you are _____.
7. Never pass the hands directly _____ the cutter knife while holding on to the stock.
8. At all times hold the _____ firmly.
9. How do you avoid end grain chip out?
10. What is the best depth of cut for surfacing hardwoods _____?
11. What is the best depth of cut for jointing (edging) hardwoods _____?
12. _____ need to be used if you are going to surface pieces thinner than 3”.
13. Explain what is meant by “Over hand feed method”.
14. When the stock is longer than twice the length of the infeed and outfeed tables, another _____ or support table must be used to support the stock.
15. When jointing an edge; you never joint a board that is less than _____ “thick.
(Over)

16. Only expose the amount of _____ that you need to cut your wood by moving the fence forward.
17. If you can, why do you want to lap your fingers above the top of your wood extending them back over the fence??
18. Rabbet cuts will _____ be made on the jointer.
19. When beveling use push blocks and applies pressure _____ the fence.
20. Explain the term “Squaring the Fence”